

System Specification	
Model	Storion-SMILE-B3
Max. AC Output Power	3000 W
Max. AC Input Power	3000 W
IP Protection	IP65
Dimension (W x D x H)	610 x 236 x 625 mm
Weight	45 kg
Operating Temperature Range	-10 °C ~ 50 °C*, 0 °C ~ 40 °C (0.5C)
Warranty	5 Year Product Warranty, 10 Year Battery Warranty
Inverter Technical Specification	
Max. AC Input Current	13 A
Nominal AC Input Voltage	230 V
Battery Voltage Range	40 V ~ 58 V
Max. Charging/Discharging Current	60 A
Max. Charging/Discharging Power	3000 W
Phase	Single-Phase
Nominal AC Output Voltage	230 V
Grid Voltage Range	180 V ~ 270 V
Rated Frequency	50/60 Hz
Backup	UPS
Grid Regulation	AS 4777.2, VDE-AR-N 4105, G83/2
Safety	IEC 62040-1, IEC 62477-1
Battery Technical Specification	
Module Capacity	2.9 kWh
Usable Capacity	2.8 kWh
Depth of Discharge (DoD)	96%
Module Nominal Voltage	51.2 V
Max. Short-circuit Current	200 A
Cycle Life	10 000 **
Max. Charging/Discharging Current	56 A (1C)
External Battery Expansion	1 ~ 5 M4856-P in parallel
Certification	UN38.3, IEC 62619 (Cell), IEC 62619 (Pack)

*When the temperature is below 0 °C or above 40 °C, the performance will be limited.
**Under specific test conditions

